| Ref # | Hits | Search Query | DBs | Default Operator | Plurals | Time Stamp |
|----------|-------|---|---|---------------------|---------|------------------|
| LI . | 82 | nail adj head and diode | US-PGPUB; USPAT; USOCR; EPO; JPO | OR | ON | 2005/03/19 14:51 |
| L2 | 27 | nail adj head same diode | US-PGPUB; USPAT; USOCR; EPO; JPO | OR | ON | 2005/03/19 14:54 |
| L3 | 332 | (257/697).CCLS. | USPAT | OR | OFF | 2005/03/19 14:54 |
| L4 | 3 | 13 and nail | USPAT | OR | OFF | 2005/03/19 14:55 |
| L5 | 9 | 13 and diode | USPAT | OR | OFF | 2005/03/19 14:58 |
| L6 | 12561 | diode and metal and housing and well | USPAT | OR | OFF | 2005/03/19 14:59 |
| L7 | 560 | diode and metal adj housing and well | USPAT | OR | OFF | 2005/03/19 14:59 |
| L8 | 189 | diode and metal adj housing and well and pin | USPAT | OR | OFF | 2005/03/19 15:20 |
| L9 | 0 | 13 and 18 | USPAT | OR | OFF | 2005/03/19 14:59 |
| L10 | 19 | pin with head and thermal with stress same thickness | USPAT | OR | OFF | 2005/03/19 15:27 |
| L11 | 89 | (pin or nail) with head same thickness and semiconductor | USPAT | OR | OFF | 2005/03/19 15:26 |
| L12 | 150 | (pin or nail) with head same thickness and semiconductor | US-PGPUB; USPAT; USOCR; EPO; JPO | OR | OFF | 2005/03/19 15:27 |
| L13 | 41 | pin with head and thermal with stress same thickness | US-PGPUB; USPAT; USOCR; EPO; JPO | OR | OFF | 2005/03/19 15:27 |